



Mechanisms supplied complete

Pack	Cat.Nos	Switches 10 AX - 250 V~	Socket outlets 20 A
10 10	0 698 51 0 698 11	IP 55 - IK 07 Automatic terminals <b>1 gang two-way switch</b> ○ White ● Grey	IP 44 - IK 08 Screw terminals <b>2P+E - 230 V~</b> ● Grey
5	0 698 55	<b>2 gang two-way switch</b> ○ White	<b>3P+E - 400 V~</b> ● Grey
5 10	0 698 61 0 698 21	<b>Push-buttons 10 A - 250 V~</b> IP 55 - IK 07 Automatic terminals <b>Illuminated changeover push-button</b> (N/O + N/C contact) Supplied with 230 V~ lamp ○ White ● Grey	<b>3P+N+E - 400 V~</b> ● Grey
5 5	0 698 64 0 698 24	<b>Illuminated changeover push-button with label-holder</b> (N/O + N/C contact) Supplied with 12 V lamp Can be equipped with 230 V~ lamp ○ White ● Grey	<b>Surface-mounting box</b> Surface-mounting box for 20 A sockets Cat.Nos 0 557 03/06/08 Dimensions: 79 x 86 x 40 mm
10 10 5	0 698 69 0 698 33 0 707 72	<b>German standard socket outlets 16 A - 250 V~</b> IP 55 - IK 07 Screw terminals <b>2P+E with earth lateral contacts</b> ○ White ● Grey ○ White antimicrobial	
5	0 707 73	<b>2P+E with earth lateral contacts, with claws</b> ○ White antimicrobial	
10 10	0 698 70 0 698 31	<b>French standard socket outlets 16 A - 250 V~</b> IP 55 - IK 07 Automatic terminals <b>2P + E with shutters for child protection</b> ○ White ● Grey	

Rigid conduits, p. 600



Video installation of Plexo

